



DIY Waterproofing and Damp-proofing solutions.

Frogskin™ Stormcryl primer

Discussion

FROGSKIN™ STORMCRYL PRIMER is a new generation water-based, penetrating and stabilising BONDING LIQUID for use in conjunction with FROGSKIN™ Roof Paint on all porous, tiled and granular surfaces as well as previously-painted substrates. FROGSKIN™ STORMCRYL PRIMER has excellent penetrating, binding and adhesive properties making it suitable for both interior and exterior applications. Whether applied to powdery, friable, porous, new or weathered surfaces, it creates an alkaline-resistant finish which dramatically improves the adhesion of FROGSKIN™ Roof Paint. FROGSKIN™ STORMCRYL PRIMER is available in 20L, 5L containers.

Physical Properties

Colour:	White milky liquid
Application:	Brush, roller or spray.
Coverage:	10-12m ² /L depending on surface porosity
Total Solids:	+/- 20%
Specific Gravity:	+/- 1
Viscosity:	<10 Krebs Units at 25°C
Cleaning:	Warm soapy water
Flammability:	Non Flammable

Surface preparation

All forms of surface contamination must be removed to ensure a smooth surface, free of moisture and any loose material, or any other barrier to adhesion.

Technical assistance and applicator training are freely available to all approved users.



DIY Waterproofing and Damp-proofing solutions.

Application

Once the surface is dry, apply one generous coat of FROGSKIN™ STORMCRYL PRIMER to the area that needs painting, using either a brush or paint roller.

Allow to dry 4-6 hours before over coating with FROGSKIN™ Roof Paint.

Do not use water to thin this primer, as thinning will reduce adhesive properties.

Do not mix with other products.

Not for use under two-pack solvent or water based products.

Do not apply before 09H00 and after 16H00 in the winter.

Do not apply if rain is imminent.

Coverage

Approx. 10 - 12 square meters per litre. Coverage does depend on the porosity of the substrate.

Clean up with warm soapy water